



1675, HAGGERTY  
DRUMMONDVILLE, QC  
Phone : (819) 478-8408  
Fax : (819) 478-0199  
E-Mail : [www.resisto.ca](http://www.resisto.ca)

<b>TECHNICAL DATA SHEET</b> <b>100222RCAN3E</b>
--

Cancels & remplace 090707RCAN1E
------------------------------------

---

## CRACK FILLER

For asphalt surfaces

---

### Description:

The **RESISTO SEAL CRACK FILLER** for asphalt surfaces is designed to repair small cracks and joints into asphalt pavement.

The **RESISTO SEAL CRACK FILLER** protects against water infiltration into asphalt pavement breakdown caused from wear, rain and freezing temperatures.

---

### Application Conditions:

- Application temperature: 10 °C (50 °F) or more. However, product can be applied at lower temperatures if conditioned at a temperature of 10 °C or more.
- Surface must be clean and dry.

---

### Packaging & Coverage:

- 300 ml tubes
- Average coverage:  
A bead of 1/4 in. (6 mm) covers approximately 29 linear feet (9 meters).

---

### General Instructions:

- Clean surface using water, let dry completely.
- Fill deep cracks using sand up to 3/8 in. (10 mm) of the top surface.
- Apply **RESISTO SEAL CRACK FILLER** using a regular caulking gun and let dry.

---

### Limitations:

- Designed for cracks up to 3/8 in. (10 mm) wide. For wider cracks, use **RESISTO SEAL LEVELING PATCH** or **ASPHALT REPAIR**.
- Allow product to cure completely before applying **RESISTO SEAL DRIVEWAY SEALER**.

**For further information, consult the Material Safety Data Sheet.**

---

### Storage:

- Maximum storage temperature: 40 °C (104 °F).
- Can support storage temperatures below 0 °C (32 °F).
- Storage conditions: 2 years in its original packaging.  
Store in a cool, well-ventilated place.

---

**NOTE :** RESISTO may modify the composition and/or utilisation of its products without prior notice. Consequently orders will be filled according to the latest specification.